ISSEMBLY INSTRUCTIONS

BiPlane

## Front\_of\_Kite **Pull Bridle Lines tight Back of Kite** before Launch. **Insert Spreaders into** Connector. **Pass Strut under Spreader** Pass Strut under Spreader and Insert into V-Connector. and Insert into V-Connector. **Insert Bottom Spreaders Insert Bottom Spreaders** into Bottom Connector. into Bottom Connector. Unwind both SkyTails® Left and Right. Attach the QuikClip® to the Bridle Loop (Front of kite).

## LAUNCHING - ASSISTED LAUNCH

Keep important information for future reference.

- The kite requires a minimum wind of 7 mph / 11.3 kph. Let out approximately 75 feet / 22.9 m of line and have an assistant hold the kite.
- With your back to the wind, release the kite and take a few steps backwards, the kite will rise into the air. Tug line to gain altitude, let out line to gain distance.
- For storage, reverse assembly steps and place into package. Store your kite in a cool dry place. Excessive heat and/or sunlight can damage the package and kite.

## KITE SAFETY

WARNING! Do not fly near overhead power lines.

WARNING! Do not use near overhead power lines or during thunderstorms.

WARNING! Not suitable for children under 3 years due to small parts.

WARNING! Not suitable for children under 3 years due to long cord.

Please remove all packaging material before giving the toy to child.

Neve Neve Neve

Never fly near an airport.

Never fly over people.

Never fly in thunderstorms.

Never fly near busy streets.

Never fly near busy streets.